



®

®

Siliseal

Waterproofing Systems

P O Box 1353
Witkoppen
2068

Tel: 082 324 5499
Fax: 011 252 6621
E-mail: siliseal@mweb.co.za
Web: www.siliseal.com

ECOBINDER

TECHNICAL DATA

| | | |
|------------------------------|---|---|
| PRODUCT DESCRIPTION | Sand particle binder | |
| INTENDED USES | Paving Ground stabilization | |
| FEATURES | Non toxic and eco friendly Bonds sand particles Prevents wind and water erosion Reduces liquid penetration Inhibits weed growth | |
| PREPARATION NEW WORKS | Conduct soil test prior to application | |
| APPLICATION | Mix ration 1:14 (EcoBinder to water) Apply by watering can, low pressure spray, water tanker or crop sprayer. Do not apply in the heat of the day, or in windy conditions | |
| CAUTION | Wear eye protection | |
| TESTS | | |
| PRODUCT INFORMATION | Colour | milky white liquid |
| | Type | water based chemical |
| | PH Value | 4 - 52 |
| | Specific weight | ,8 kg/lt |
| | Spreading Rate | 0.5 -2 m ² /lt depending of particle size and porosity |
| SPECIFICATIONS | EcoBinder | |
| | Weight % | 30 |
| | Form | liquid |
| | PH | 8 |
| DURABILITY | Testing is recommended due to varying site conditions | |
| PACKAGING | 1lt, 5lt, 10lt, 20lt, 200lt | |

The application, handling and conditions of use of our products are critical and beyond our control. Information given by us in our documentation orally, or by any employee or distributor and any advice, recommendation or assistance is given in good faith but without creating any obligation or warranty.