



®

®

Siliseal

Waterproofing Systems

P O Box 1353
Witkoppen
2068

Tel: 082 324 5499
Fax: 011 252 6621
E-mail: siliseal@mweb.co.za
Web: www.siliseal.com

PLASTERKEY

TECHNICAL DATA

PRODUCT DESCRIPTION

Water based bonding agent

INTENDED USES

Plasterkey is designed specifically to bond sand / cement plaster and gypsum plaster to surfaces.

FEATURES

Improves non-structural bond of cement and gypsum plasters.
Bonds to sound PVA surfaces.
Plasterkey is easy to use and avoids any future hacking or chipping of smooth surfaces.

PREPARATION NEW WORKS

Surfaces should be free of loose particles, scaling or flaking materials
Wire brush and rinse the surface where necessary.

APPLICATION

Mix thoroughly prior to use

Soffits and Vertical surfaces:

Remove all dust from surfaces and coat with **Plasterkey**
Apply a scratch coat whilst the **Plasterkey** is still wet
Once **Plasterkey** is dry, plaster in usual manner

Gypsum based Plaster:

Apply **Plasterkey** to the prepared surface
Plaster straight onto the wet **Plasterkey** finishing off in a single operation.

Plasterkey can be added to plaster mix (10% of water content) to strengthen bond.
Applied by brush or roller

PRODUCT INFORMATION

Curing 3 – 12 hours depending on mixture
Spreading Rate 10 m²/lt depending on the surface

STORAGE

Plasterkey must be kept in an airtight container and stored at a moderate temperature
Prior to use ensure the mixture is mixed

PACKAGING

1lt, 5lt, 10lt, 20lt

The application, handling and conditions of use of our products are critical and beyond our control. Information given by us in our documentation orally, or by any employee or distributor and any advice, recommendation or assistance is given in good faith but without creating any obligation or warranty.