



®

®

Siliseal

Waterproofing Systems

P O Box 1353
Witkoppen
2068

Tel: 082 324 5499
Fax: 011 252 6621
E-mail: siliseal@mweb.co.za
Web: www.siliseal.com

TILE BOND

TECHNICAL DATA

PRODUCT DESCRIPTION

Additive used with tile grout and tile adhesive

INTENDED USES

Smooth trowelled wall and floor areas, cold rooms and walls where temperature changes are experienced

Can also be used as a priming / sealing coat for gypsum, asbestos and cement surfaces.

Tile Bond has strengthening and waterproofing properties and can be used in conjunction with tile adhesive and tile grout where increased bond strength is required.

FEATURES

Specially formulated for interior and exterior use

Replaces water in mix with **Tile Bond** when using cement based adhesives and grout.

Allows for minimal movement when added to materials

Water resistant and can be used where permanently wet conditions exist

PREPARATION NEW WORKS

Ensure surface is free of loose materials, mould oil, grease or organic growth

Use an effective fungicide.

APPLICATION

Mix thoroughly prior to use

When used as primer, apply until surface is saturated.

Leave for a minimum of 1 hour to a maximum of 48 hours before tiling or coating

Cement based adhesives and grout will dry a shade darker with the addition of **Tile Bond**.

Allow 12 hours to dry

PRODUCT INFORMATION

Curing 3 – 12 hours depending on the mixture

Spreading Rate refer to applicable product used along with **Tile Bond**

STORAGE

Tile Bond must be kept in an airtight container and stored at a moderate temperature

PACKAGING

1lt, 5lt, 10lt, 20lt